PATENT 450100-05166

U.S. Apln. No. 10/564,465 Supplemental Response

IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the

application. An identifier indicating the status of each claim is provided.

Listing of Claims:

(Currently Amended) An encryption apparatus, comprising:

hold means for holding a part or all input data with a trigger signal and resetting held data

with a reset signal;

one or a plurality of counters that count up or count down count values with the trigger

signal and reset the count values to predetermined values with the reset signal;

encryption means for reading the data held by the hold means and one or a plurality of

the count values and for encrypting the data held by the hold means and one or a plurality of the

count values of the one or plurality of counters;

calculation means for calculating the output of the encryption means and input data that

are input from the outside according to a first predetermined rule, encrypting the input data, and

outputting the encrypted data;

a path that inputs a part or all the encrypted data that are output from the calculation

means to the hold means; and

signal generation means for generating the trigger signal and the reset signal supplied to

the hold means and the one or plurality of counters according to a second predetermined rule

and/or at predetermined timing.

Frommer Lawrence & Haug LLP 745 Fifth Avenue New York NY 10151

212-588-0800

-Page 3 of 14-00615948 2. (Original) The encryption apparatus as set forth in claim 1,

wherein a fixed value is input to the encryption means, and

wherein the encryption means encrypts the fixed value, the data held by the hold means, and the one or plurality of count values.

3. (Original) The encryption apparatus as set forth in claim 1.

wherein the reset signal that resets the data held by the hold means is supplied to the hold means at timing in synchronization with the reset signal supplied to at least one of the one or plurality of counters.

4. (Original) The encryption apparatus as set forth in claim 1,

wherein the input data are picture data, and

wherein the reset signal that resets the hold means is in synchronization with the picture data.

5. (Original) The encryption apparatus as set forth in claim 4,

wherein the reset signal that resets the hold means is in synchronization with each line of the picture data.

6. (Original) The encryption apparatus as set forth in claim 1,

wherein the input data are picture data, and

wherein the reset signal that resets at least one of the one or plurality of counters is in synchronization with the picture data. 7. (Original) The encryption apparatus as set forth in claim 6,

wherein the reset signal that resets at least one of the one or plurality of counters is in synchronization with each frame of the picture data.

8. (Original) The encryption apparatus as set forth in claim 6,

wherein the reset signal that resets at least one of the one or plurality of counters is in synchronization with each line of the picture data.

9. (Currently Amended) An encryption method, comprising the steps of:

holding a part or all input data with a trigger signal and resetting held data with a reset signal;

counting up or down count values with the trigger signal and resetting the count values to predetermined values with the reset signal;

reading the data held by the hold step and one or a plurality of the count values;

encrypting the data held at the hold step and one or a plurality of the count values at the count step;

calculating the output at the encryption step and input data that are input from the outside according to a first predetermined rule, encrypting the input data, and outputting the encrypted data;

inputting a part or all the encrypted data that are output at the calculation step to the hold step; and

PATENT 450100-05166

U.S. Apln. No. 10/564,465 Supplemental Response

generating the trigger signal and the reset signal supplied to the hold step and the count

10. (Canceled)

11. (Currently Amended) A record medium storing an executable program that, when

executed, causes a computer to encrypt data, the program comprising the steps of:

step according to a second predetermined rule and/or at predetermined timing.

holding a part or all input data with a trigger signal and resetting held data with a reset

signal;

counting up or down count values with the trigger signal and resetting the count values to

predetermined values with the reset signal;

reading the data held by the hold step and one or a plurality of the count values;

encrypting the data held at the hold step and one or a plurality of the count values at the

count step;

calculating the output at the encryption step and input data that are input from the outside

according to a first predetermined rule, encrypting the input data, and outputting the encrypted

data:

inputting a part or all the encrypted data that are output at the calculation step to the hold

step; and

generating the trigger signal and the reset signal supplied to the hold step and the count

step according to a second predetermined rule and/or at predetermined timing.

Frommer Lawrence & Haug LLP 745 Fifth Avenue New York, NY 10151

212-588-0800

-Page 6 of 14- 00615948

PATENT 450100-05166

U.S. Apin. No. 10/564,465 Supplemental Response

12. (Currently Amended) A decryption apparatus that decrypts encrypted data

encrypted by an encryption apparatus, the decryption apparatus comprising:

hold means for holding a part or all input data with a trigger signal and resetting held data

with a reset signal;

one or a plurality of counters that count up or count down count values with the trigger

signal and reset the count values to predetermined values with the reset signal;

encryption means for reading the data held by the hold means and one or a plurality of

the count values and for encrypting the data held by the hold means and one or a plurality of the

count values of the one or plurality of counterseneryption means for encrypting the data held by

the hold means and one or a plurality of count values of the one or plurality of counters;

calculation means for calculating the output of the encryption means and input data that

are input from the outside according to a first predetermined rule, encrypting the input data, and

outputting the encrypted data;

a path that inputs a part or all the encrypted data that are input from the outside to the

hold means; and

signal generation means for generating the trigger signal and the reset signal supplied to

the hold means and the one or plurality of counters according to a second predetermined rule

and/or at predetermined timing.

13. (Original) The decryption apparatus as set forth in claim 12,

wherein a fixed value is input to the encryption means, and

wherein the encryption means encrypts the fixed value, the data held by the hold means,

-Page 7 of 14-

and the one or plurality of count values.

Frommer Lawrence & Haug LLP 745 Fifth Avenue U.S. Apln. No. 10/564,465 PATENT Supplemental Response 450100-05166

14. (Original) The decryption apparatus as set forth in claim 12,

wherein the reset signal that resets the data held by the hold means is supplied to the hold means at timing in synchronization with the reset signal supplied to at least one of the one or plurality of counters.

(Original) The decryption apparatus as set forth in claim 12.

wherein the encrypted data are encrypted picture data, and

wherein the reset signal that resets the hold means is in synchronization with the picture

(Original) The decryption apparatus as set forth in claim 15,

wherein the reset signal that resets the hold means is in synchronization with each line of the picture data.

17. (Original) The decryption apparatus as set forth in claim 12,

wherein the encrypted data are encrypted picture data, and

wherein the reset signal that resets at least one of the one or plurality of counters is in synchronization with the picture data.

18. (Original) The decryption apparatus as set forth in claim 17,

wherein the reset signal that resets at least one of the one or plurality of counters is in synchronization with each frame of the picture data. 19. (Original) The decryption apparatus as set forth in claim 17,

wherein the reset signal that resets at least one of the one or plurality of counters is in synchronization with each line of the picture data.

 (Currently Amended) A decryption method of decrypting encrypted data encrypted in an encryption method, the decryption method comprising the steps of:

holding a part or all input data with a trigger signal and resetting held data with a reset signal;

counting up or down the count values with the trigger signal and resetting count values to predetermined values with the reset signal;

reading the data held by the hold step and one or a plurality of the count values:

encrypting the data held at the hold step and one or a plurality of <u>the</u> count values at the count step;

calculating the output at the encryption step and input data that are input from the outside according to a first predetermined rule, encrypting the input data, and outputting the encrypted data:

inputting a part or all the encrypted data that are input from the outside to the hold step;

generating the trigger signal and the reset signal supplied to the hold step and the count step according to a second predetermined rule and/or at predetermined timing.

## 21. (Canceled)

U.S. Apln. No. 10/564,465 PATENT Supplemental Response 450100-05166

22. (Currently Amended) A record medium storing an executable program that, when

executed, causes a computer to decrypt data, the program comprising the steps of:

holding a part or all input data with a trigger signal and resetting held data with a reset

signal;

counting up or down the count values with the trigger signal and resetting count values to

predetermined values with the reset signal;

reading the data held by the hold means and one or a plurality of the count values;

encrypting the data held at the hold step and one or a plurality of the count values at the

count step;

calculating the output at the encryption step and input data that are input from the outside

according to a first predetermined rule, encrypting the input data, and outputting the encrypted

data:

inputting a part or all the encrypted data that are input from the outside to the hold step;

and

generating the trigger signal and the reset signal supplied to the hold step and the count

step according to a second predetermined rule and/or at predetermined timing.

Frommer Lawrence & Haug LLP 745 Fifth Avenue New York, NY 10151 212-588-0800

-Page 10 of 14-

00615948